

XKPR

Reader for pedestrian and vehicular access control

Type of reader

passive proximity
keyboard

Installation

wall or column



XKPR 125



XKPR 1356

- Suitable for outdoor installations
- Aluminum case, steel keyboard and cover
- Compact, solid, slim: suitable for all architectural contexts



TECHNICAL SPECIFICATIONS

Model	XKPR 125	XKPR 1356
Enclosure	metal	
Operating ambient temperature	-20 °C +55 °C	
Dimensions (LxDxH)	72x28x100 mm	
Connection	Bi-directional BUS (for connection to the Door Controller)	
Number of high brightness LED	1 bi-color (red & green)	
Protection class	IP54	
Technology	125 KHz	13.56 MHz MIFARE
Buzzer	Yes	
Keypad	Metal 12-key keyboard with backlighting	
Installation type	wall or on column installation	

FAMILY MODELS

Model	Description	Item code
XKPR 125	Proximity 125 KHz + Keyboard	105907
XKPR 1356	Mifare proximity 13.56 MHz + Keyboard	105922

ELECTRONIC CONTROL UNITS



Door Controller LAN/
RS485

202323

ACCESSORIES



External tube adapter

401064



High column in
aluminium
(2 pcs. pack)

401034



Foundation plate for
aluminium column
(T10-T11-T10 E-T11 E)
(20 pcs. pack)

737630



100 m skein of SPI net
bus cable. Composed of
2 twisted pairs of 0.50
mm²

S-CAVO-BUS