



DIGITAL
PADLOCKS
SMART INTEGO

DIGITAL PADLOCK SMART INTEGO



// TECHNICAL DATA

- ∴ Version 8 mm shackle diameter
Dimensions:
(W x H x D) without cylinder knob 51 x 70 x 25 mm
- ∴ Version 11 mm shackle diameter
Dimensions:
(W x H x D) without cylinder knob 60 x 72.5 x 25 mm
- ∴ Shackle diameter: 8 / 11 mm
- ∴ Versions:
ML: Not self-locking
SL: Self-locking
- ∴ Shackle height: 25 mm, 50 mm, 60 mm
- ∴ Standard protection rating IP 66,
- ∴ Battery type: 2 x lithium CR2450 3V Lithium
- ∴ Battery lifetime:
Wireless Online: up to 80,000 closures
Virtual Card Network: up to 50,000 closures
Wireless Online Stand-by: up to 5 years
Virtual Card Network Stand-by: up to 5 years
- ∴ Temperature range:
operation -25 °C to +65 °C

// WIRELESS ONLINE (868 MHZ)

- ∴ Reads 5 different card set-ups
- ∴ Opened after release by access control system (short release interval) with variable time settings
- ∴ Permanent release (on/off) with timer function
- ∴ Office mode with timer function
- ∴ White List function with up to 250 offline cards
- ∴ Recording of accesses even in the event of network failure
- ∴ Transmission of battery status and QoS (quality of signal)
- ∴ Configurable "keep alive" event
- ∴ Construction White List function with up to 128 cards
- ∴ 'Integrator lock'
- ∴ Auto-configuration via SmartIntego Manager (in TCP/IP Gateway Node models only)

// VIRTUAL CARD NETWORK

- ∴ Issue of authorisations (access) based on doors, areas, groups and exception functions
- ∴ Battery status
- ∴ Office mode with "timer" function
- ∴ Physical access lists
- ∴ Time budget / activation and expiration date
- ∴ Data deletion on online terminal
- ∴ Initial programming possible using access control manufacturer's online reader
- ∴ Time profiles on the card
- ∴ Data transmission secured during writing and read procedure

DIGITAL
PADLOCK
SMART INTEGO

// BASIC VERSIONS

Description	WIRELESS ONLINE Order code	VIRTUAL CARD NETWORK Order code
<p>Digital Padlock SmartIntego with a shackle diameter of 8 mm and shackle internal height of 25 mm, internal power supply; locking device operated from outside with SmartCards/SmartTags; no wiring required; padlock dimensions: (W x H x D) without cylinder knob 51 x 70 x 25 mm</p> <p>Manual locking:</p> <p>Self-locking</p>	<p>SI.Z4.PL.08.25.MI.ML.WP</p> <p>SI.Z4.PL.08.25.MI.SL.WP</p>	<p>SI.Z4.PL.08.25.M.ML.WP</p> <p>SI.Z4.PL.08.25.M.SL.WP</p>
<p>Digital Padlock SmartIntego with a shackle diameter of 8 mm and shackle internal height of 60 mm, internal power supply; locking device operated from outside with SmartCards/SmartTags; no wiring required; padlock dimensions: (W x H x D) without cylinder knob 60 x 72.5 x 25 mm</p> <p>Manual locking:</p> <p>Self-locking</p>	<p>SI.Z4.PL.08.60.MI.ML.WP</p> <p>SI.Z4.PL.08.60.MI.SL.WP</p>	<p>SI.Z4.PL.08.60.M.ML.WP</p> <p>SI.Z4.PL.08.60.M.SL.WP</p>
<p>Digital Padlock SmartIntego with a shackle diameter of 11 mm and shackle internal height of 35 mm, internal power supply; locking device operated from outside with SmartCards/SmartTags; no wiring required; padlock dimensions: (W x H x D) without cylinder knob 60 x 72.5 x 25 mm</p> <p>Manual locking:</p>	<p>SI.Z4.PL.11.35.MI.ML.WP</p>	<p>SI.Z4.PL.11.35.M.ML.WP</p>
<p>Digital Padlock SmartIntego with a shackle diameter of 11 mm and shackle internal height of 50 mm, internal power supply; locking device operated from outside with SmartCards/SmartTags; no wiring required; padlock dimensions: (W x H x D) without cylinder knob 60 x 72.5 x 25 mm</p> <p>Self-locking</p>	<p>SI.Z4.PL.11.50.MI.SL.WP</p>	<p>SI.Z4.PL.11.50.M.SL.WP</p>
ACCESSORIES		
<p>Securing chain for padlock, shackle 11 mm in diameter, Length: about 30 cm</p>	<p>PL.CHAIN.11.30</p>	<p>PL.CHAIN.11.30</p>
<p>Securing chain for padlock, shackle 8 mm in diameter, Length: about 30 cm</p>	<p>PL.CHAIN.08.30</p>	<p>PL.CHAIN.08.30</p>
<p>Wall bracket for securing chain</p>	<p>PL.CHAIN.BRACKET</p>	<p>PL.CHAIN.BRACKET</p>

